





1/9



BEST AVAILABLE COPY

2/9

**Performance Testing
for
Recycled Rubber Replacement Soil Based Turf Growing Medium**

Test Description	Trial No. 1	Specification Acceptance Range
Field Testing	2/8/01	
Football Rebound Resilience	50%	20 to 50%
Clegg Impact Soil Tester Rating	20	20 to 80g
Traction	42 N.m	Minimum 25 N.m Preferred
Distance Rolled by a Football	4.1m	3 to 12m Preferred
Surface Evenness	3.0mm	Maximum 8mm Standard Deviation Preferred
Depth of Grass	20mm	
Type of Grass	Kikuyu	
Thickness of Rubber Profile	75 to 80mm	
Ball	REAL: Size 5:437.8g+	

Notes:

- Specifications from Standards for the Playing Quality of Natural Turf for Association Football by P.M Canaway, M.J Bell, G Holmes and S.W. Baker
- + Calibrated inflation to rebound between 57 to 59% when dropped onto concrete and a drop height of 3m.
- Clegg Impact Hammer: Mass 0.5kg ; Drop 300mm ; 50mm Diameter
- Weather conditions: Fine, dry and between 17 to 20° Celcius
- The rubber soil profile was moist and the test area was made up 1.1m square plates of the grass rubber soil profile

Fig. 3

3/9

**Performance Testing
for
Recycled Rubber Replacement Soil Based Turf Growing Medium**

Test Description	Trial No. 2	Specification Acceptance Range
Field Testing	2/8/01	
Football Rebound Resilience	49%	20 to 50%
Clegg Impact Soil Tester Rating	15	20 to 80g
Traction	59 N.m	Minimum 25 N.m Preferred
Distance Rolled by a Football	4.1m	3 to 12m Preferred
Surface Evenness	2.3mm	Maximum 8mm Standard Deviation Preferred
Depth of Grass	20mm	
Type of Grass	Kikuyu	
Thickness of Rubber Profile	90mm	
Ball	REAL: Size 5:437.8g+	

Notes:

- Specifications from Standards for the Playing Quality of Natural Turf for Association Football by P.M Canaway, M.J Bell, G Holmes and S.W. Baker
- + Calibrated inflation to rebound between 57 to 59% when dropped onto concrete and a drop height of 3m.
- Clegg Impact Hammer: Mass 0.5kg ; Drop 300mm ; 50mm Diameter
- Weather conditions: Fine, dry and between 17 to 20° Celcius
- The rubber soil profile was moist and the test area was made up 1.1m square plates of the grass rubber soil profile

Fig. 4

4/9

**Performance Testing
for
Recycled Rubber Replacement Soil Based Turf Growing Medium**

Test Description	Trial No.3	Specification Acceptance Range
Field Testing	2/8/01	
Football Rebound Resilience	45%	20 to 50%
Clegg Impact Soil Tester Rating	22	20 to 80g
Traction	42 N.m	Minimum 25 N.m Preferred
Distance Rolled by a Football	-	3 to 12m Preferred
Surface Evenness	3mm	Maximum 8mm Standard Deviation Preferred
Depth of Grass	15mm	
Type of Grass	Couch	
Thickness of Rubber Profile	70mm	
Ball	REAL: Size 5:437.8g+	

Notes:

- Specifications from Standards for the Playing Quality of Natural Turf for Association Football by P.M Canaway, M.J Bell, G Holmes and S.W. Baker
- + Calibrated inflation to rebound between 57 to 59% when dropped onto concrete and a drop height of 3m.
- Clegg Impact Hammer: Mass 0.5kg ; Drop 300mm ; 50mm Diameter
- Weather conditions: Fine, dry and between 17 to 20° Celcius
- The rubber soil profile was moist and the test area was made up 1.1m square plates of the grass rubber soil profile

Fig. 5

5/9

Performance Testing
of
Turf Growing Medium

Test Description	Trial Rubber	Trial SFS	Trial SCG	Specification Acceptance Range
Field Testing	2/8/01	16/8/01	16/8/01	
Football Rebound Resilience	50 %	38 %	45 %	20 to 50%
Clegg Impact Soil Tester Rating	20 g	13 g	16 g	20 to 80g
Traction	42 N.m	55 N.m	65 N.m	Minimum 25 N.m Preferred
Distance Rolled by a Football	4.1 m	3.8 m	4.7 m	3 to 12m Preferred
Surface Evenness	3.0 mm	4.8 mm	1.8 mm	Maximum 6mm Standard Deviation Preferred
Type of Profile	Rubber	Sand/Soil	Sand	
Depth of Grass	20 mm	20mm to 35mm	25mm to 30mm	
Type of Grass	Kikuyu	Couch Legend	Couch Legend	
Thickness of Soil Profile	75mm to 80mm	> 300 mm	300mm	
Ball	REAL: Size 5:437.8g+			

Fig. 6

6/9

resilience test results




Fig. 7

7/9




Fig. 8

Fig. 9




Fig. 10

9/9




Fig. 11

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.